

## Barometric Pressure Smart Sensor (S-BPA-CM10) Quick Start

---

### **Connecting to a Station**

1. Stop the station if it is logging
  2. Plug the smart sensor jack into an open smart sensor port on the station.
  3. Start logging. See the station manual at [www.onsetcomp.com/support/manuals](http://www.onsetcomp.com/support/manuals) for details on operating stations with smart sensors.
- 

### **Mounting the Smart Sensor**

- The barometric pressure smart sensor must be used inside the logger enclosure. Use the hook-and-loop tape to affix it to the inside of the logger enclosure.
  - The sensor measures air pressure inside the logger enclosure. The vent in the enclosure must be free from obstructions for the sensor to function correctly.
- 



*For more information about this smart sensor, refer to the full product manual. Scan the code at left or go to [www.onsetcomp.com/support/manuals/s-bpa](http://www.onsetcomp.com/support/manuals/s-bpa).*

---



1-800-LOGGERS (564-4377) • 508-759-9500  
[www.onsetcomp.com/support/contact](http://www.onsetcomp.com/support/contact)

© 2017 Onset Computer Corporation. All rights reserved. Onset and HOBO are registered trademarks of Onset Computer Corporation. All other trademarks are the property of their respective companies.

21828-A MAN-S-BPA-QSG